



# NTN BEARING DRIVESHAFT, INC.



2.953 Inch | 75 Millimeter x 5.118 Inch | 130 Millimeter x 0.984 Inch | 25 Millimeter SKF NUP 215 ECM/C3 Cylindrical Roller Bearings

Bearing No. NUP 215 ECM/C3

NUP 215 ECM/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	1.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.574
EAN	7316577035288
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	No
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity   1 Rib Inner Ring with Side Plate   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	75MM Bore; Straight Bore Profile; 130MM Outside



## NTN BEARING DRIVESHAFT,INC.

	Diameter; 25MM Width; Brass Cage Material; RBEC 1   ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C3-Loose Internal Clearance; Retai
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	NUP 215 ECM/C3
Weight / LBS	3.466
d	2.953 Inch   75 Millimeter
B	0.984 Inch   25 Millimeter
D	5.118 Inch   130 Millimeter
bore diameter:	75 mm
static load capacity:	156 kN
outside diameter:	130 mm
precision rating:	Not Rated
overall width:	25 mm
maximum rpm:	6000 RPM
flanges:	(4) Flanges, Two-Piece Inner Ring
bearing material:	Steel
bore type:	Straight
cage material:	Brass
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Ring
outer ring width:	25 mm
operating temperature	Maximum of +300 ° F



## NTN BEARING DRIVESHAFT, INC.

range:	
fillet radius:	1.5 mm
dynamic load capacity:	150 kN
series:	NUP2