



NTN BEARING DRIVESHAFT,INC.



5.906 Inch | 150 Millimeter x 8.858 Inch | 225 Millimeter x 1.378 Inch | 35 Millimeter SKF NU 1030 ML/C3 Cylindrical Roller Bearings

Bearing No. NU 1030 ML/C3

NU 1030 ML/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	2.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	4.995
EAN	7316577727848
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	150MM Bore; Straight Bore Profile; 225MM Outside Diameter; 35MM Width;



NTN BEARING DRIVESHAFT,INC.

	Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Inte
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 1030 ML/C3
Weight / LBS	11.003
d	5.906 Inch 150 Millimeter
D	8.858 Inch 225 Millimeter
B	1.378 Inch 35 Millimeter
bore diameter:	150 mm
static load capacity:	290 kN
outside diameter:	225 mm
precision rating:	Not Rated
overall width:	35 mm
maximum rpm:	5000 RPM
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
outer ring width:	35 mm
ring separation:	Separable Ring
fillet radius:	2 mm
operating temperature range:	Maximum of +300 ° F



NTN BEARING DRIVESHAFT, INC.

series:	NU10
dynamic load capacity:	198 kN